


SCHUNK ROTA-G 400


Zachte klauwen (nok/groef)



recht


TYPE	A	B	C	D	K	R	S	BOUT	KG/SET	MATERIAAL
CU32	145	60	40	12	54	45	26	M12	6.8	staal
CU321	110	60	40	12	54	30	26	M12	4.9	staal
CU323	145	100	40	12	54	30	26	M12	11.1	staal
CU324	145	125	40	12	54	30	26	M12	13.9	staal
CU325	145	150	40	12	54	30	26	M12	16.9	staal
CU326	110	60	60	12	54	30	26	M12	7.6	staal
DP32	100	60	80	12	54	30	26	M12	8.4	staal
CU328	110	80	80	12	54	30	26	M12	14.1	staal
CU329	145	80	50	12	54	30	26	M12	11.6	staal
CW32	145	60	40	12	54	45	26	M12	2.4	aluminium

segment omkeerbaar




TYPE	A	B	C	D	K	R	S	BOUT	KG/SET	MATERIAAL
CQ32	132	76	240	12	54		26	M12	28.0	staal
HT32	133	76	240	12	54		26	M12	10.5	aluminium

segment



TYPE	A	B	C	D	K	R	S	BOUT	KG/SET	MATERIAAL
CF32	148	51	305Ø	12	54		26	M12	23.0	staal


Harde klauwen (nok/groef)



grijpklauwen - buitenspanning


TYPE	SPANBEREIK	GRONDKLAUW POSITIE	B	C	D	K	S	B	T	KG/SET
LY40	68 - 186	1	59	50	12	54	26	25	M8	4.0
	142 - 263	2								
LY43	192 - 313	1								3.2
	269 - 391	2								

omkeerbaar




TYPE	A	B	C	D	K	S	T	BOUT	KG/SET
GX32	105	62	36	12	54	26	15	M12	3.2

Grondklauwen



TYPE	A	B	C	D	K	S	BOUT	KG/SET
GBK400	125	43	32	12	54	26	M12	3.0

Zachte monoblok klauwen



TYPE	A	B	C	h	KG/SET
UVB400	145	100	32	66	9.0