



Zachte klauwen (nok/groef)



recht

| TYPE | A | B | C | D | K | R | S | BOUT | KG/SET | MATERIAAL |
|-------|-----|-----|----|----|----|----|----|------|--------|-----------|
| CU40 | 180 | 80 | 50 | 18 | 60 | 50 | 30 | M16 | 11.2 | staal |
| CU401 | 130 | 80 | 60 | 18 | 60 | 35 | 30 | M16 | 11.9 | staal |
| CU402 | 180 | 80 | 60 | 18 | 60 | 35 | 30 | M16 | 16.5 | staal |
| CU403 | 155 | 100 | 60 | 18 | 60 | 35 | 30 | M16 | 15.3 | staal |
| CU404 | 155 | 125 | 60 | 18 | 60 | 35 | 30 | M16 | 18.7 | staal |
| DP40 | 130 | 80 | 80 | 18 | 60 | 35 | 30 | M16 | 16.2 | staal |
| CU406 | 155 | 160 | 50 | 18 | 60 | | 30 | M16 | 25.2 | staal |
| CW40 | 180 | 100 | 51 | 18 | 60 | 50 | 30 | M16 | 6.3 | aluminium |
| CU407 | 155 | 80 | 80 | 18 | 60 | 35 | 30 | M16 | 19.3 | staal |


Harde klauwen (nok/groef)



omkeerbaar


| TYPE | A | B | C | D | K | S | T | BOUT | KG/SET |
|------|-----|----|----|----|----|----|----|------|--------|
| GX40 | 130 | 80 | 45 | 18 | 60 | 30 | 20 | M16 | 10.8 |

Grondklauwen



| TYPE | A | B | C | D | K | S | BOUT | KG/SET |
|--------|-----|----|----|----|----|----|------|--------|
| GBK500 | 160 | 57 | 45 | 18 | 60 | 30 | M16 | 7.1 |

Zachte monoblok klauwen



| TYPE | A | B | C | h | KG/SET |
|--------|-----|-----|----|----|--------|
| UVB500 | 175 | 134 | 45 | 87 | 19.5 |